

FireWire/USB 2.0 Lighted Combo



Western Digital External Hard Drives

INTERFACE

FireWire®,
IEEE 1394, 1394a,
i.LINK

USB 2.0 and 1.1

CAPACITIES

120 and 250 GB

SYSTEM REQUIREMENTS

Macintosh®
Available OHCI-compliant
FireWire enabled or
USB 2.0 or 1.1 port,
Mac OS v9.2.2 or later;
built for Mac OS X

Windows®
Available OHCI-compliant
FireWire enabled or
USB 2.0 or 1.1 port,
Windows 98SE or higher

ORDER NUMBERS

WDXC1200JBRNx
WDXC2500JBRNx

Western Digital's FireWire/USB 2.0 Lighted Combo drives make it easy to add instant, high-speed storage to your PC or Macintosh. With capacities up to 250 GB and an 8 MB buffer, you can quickly and easily make room to store your growing digital photo album collection, transfer large digital video movies, or back up valuable personal data. Designed with a contemporary, clear, light-up case and a built-in WD Caviar® SE 7200 RPM hard drive, this external storage solution combines a high-tech look, with high performance, reliability, and the versatility of dual interfaces.

Product Features

- High-tech design – stackable, light-up case.
- Versatile – features both FireWire and USB 2.0 and 1.1 interface connections; works with both Windows and Macintosh systems.
- Instant storage – preformatted*; simply plug it in and begin storing files.
- Fast – 7200 RPM and 8 MB cache performance for smooth digital video editing.
- Hot-swappable – connect and disconnect without powering off the computer.
- Guaranteed compatibility – backed by WD's commitment to data protection and award-winning customer support and services.

Applications

- Add plenty of storage for digital video capture and editing.
- Save your CD collection and create your own personal digital music jukebox.
- Add lots of storage to organize the massive amount of data generated by today's digital devices such as MP3 players, digital cameras, and DV camcorders.
- Back up all of your important files on one, easily accessible drive.
- Share files between computers.
- Add virtually unlimited storage space with multiple external hard drives.

Kit Contents

- FireWire/USB 2.0 Lighted Combo drive
- 6 foot (1.8m) 6-pin to 6-pin FireWire interface cable
- 6 foot (1.8m) USB 2.0 certified interface cable
- AC adapter with power cord
- Quick Install guide
- 1-year warranty

IMPORTANT: A USB 2.0 host and USB 2.0 certified cable are required for Hi-Speed USB performance.

* Preformatted for Windows. Simple Macintosh formatting instructions included.

FireWire/USB 2.0 Lighted Combo



Western Digital External Hard Drives

System Requirements

Macintosh

- Available OHCI-compliant FireWire and/or USB 1.1 port
- Mac OS v9.2.2 or later; built for Mac OS X

Windows

- Available OHCI-compliant FireWire and/or USB 2.0 or 1.1 port
- Windows 98SE/Me/2000/XP

Drive Specifications

	120 GB	250 GB
Formatted capacity ²	120,034 MB	250,059 MB
Actuator type	Rotary voice coil	Rotary voice coil
Servo type	Embedded	Embedded
Dedicated landing zone	Yes	Yes
Actuator latch/auto park	Yes	Yes

Performance Specifications

Average read seek	8.9 ms average
Track-to-track seek	2.0 ms average
Average latency	4.2 ms nominal
Rotational speed	7200 RPM
Buffer	8 MB

Physical Dimensions

Height	1.74 in. (44.20 mm) ± .10
Length	8.61 in. (218.75 mm) ± .10
Width	6.08 in. (154.43 mm) ± .10

Packaging Specifications

	English / Imperial
Retail box size	11.75 in. x 6.5 in. x 10.0 in.
Retail box weight	6.0 lbs
Master carton size	13.25 in. x 10.875 in. x 12.625 in.
Master carton weight	12.0 lbs
Boxes per master carton	2
Master cartons per pallet	60

Retail UPC Codes

Capacity	Model Number	Order Number	UPC Code
250 GB (US)	WD2500B007-RNN	WDXC2500JBRNN	7 18037 10545 1
250 GB (Europe)	WD2500B007-RNE	WDXC2500JBRNE	7 18037 10546 8
250 GB (UK)	WD2500B007-RNN	WDXC2500JBRNN	7 18037 10547 5
120 GB (US)	WD1200B007-RNN	WDXC1200JBRNN	7 18037 10536 9
120 GB (Europe)	WD1200B007-RNE	WDXC1200JBRNE	7 18037 10537 6
120 GB (UK)	WD1200B007-RNU	WDXC1200JBRNU	7 18037 10538 3

Interface Specifications

FireWire

- FireWire, IEEE 1394, i.LINK
- OHCI and SBP-2 compliant
- Two external 6-pin 1394 receptacles
- Serial bus data transfer rates of 100, 200, and 400 Mb/sec

USB 2.0

- USB 2.0 and 1.1 compliant ¹
- One external "B" 4-pin USB receptacle
- Serial bus data transfer rates of up to 480 Mb/sec

Environmental Specifications

Operating temperature	0°C to 40°C
Non-operating temperature	-20°C to 65°C

Power Requirements

AC input voltage	100-240 VAC
AC input frequency	50-60 Hz
AC input current	0.6A max (RMS)



For service and literature:

800.ASK.4WDC North America
 949.672.7199 Spanish
 +800.6008.6008 Asia Pacific
 +31.20.4467651 EMEA
 support.wdc.com
 www.westerndigital.com

Western Digital and WD Caviar are registered trademarks and WD and the WD logo are trademarks of Western Digital Technologies, Inc. Other marks may be mentioned herein that belong to other companies. Product and packaging specifications subject to change without notice.

© 2004 Western Digital Technologies, Inc. All rights reserved.

Western Digital
 20511 Lake Forest Drive
 Lake Forest, California 92630

2879-001073-A03 10/04

¹ A USB 2.0 host and USB 2.0 certified cable are required to obtain Hi-Speed USB performance.

² This capacity is reported using the decimal numbering system (1 MB = 1,000,000 bytes and 1 GB = 1,000,000,000 bytes). Both Windows and Macintosh operating systems use the binary numbering system, which results in a lower reported capacity.