



2.5-inch U.2, 15mm, NVMe SSD  
1.60TB, 1.92TB, 3.20TB, 3.84TB, 6.4TB, 7.68TB<sup>1</sup>

## Highlights

- Experience exceptional PCIe Gen5 performance in multiple capacities up to 7.68TB<sup>1</sup>, perfect for compute-intensive applications
- Engineered for minimal power consumption, optimizing efficiency and reducing operational costs without compromising performance
- Achieve optimized solutions at low cost for your enterprise's mixed workloads with high-speed random read performance
- Delivering consistent QoS, even under heavy workloads, helping latency during mission-critical operations
- E1.S options also available, ensuring scalability and flexibility to meet your enterprise storage needs
- Benefit from enterprise-class features including Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, all backed by a 5-year limited warranty<sup>6</sup>

## Applications/Environments

- Hyperscale Cloud and Enterprise Datacenters
- Compute Intensive Applications
- Standard Compute, High CPU, High GPU, HPC Workloads
- Big Data, Data Analytics, Data Modeling, Predictive Analysis
- AI/ML, Deep Learning

## Redefining the limits for high-performance storage

Be ready for the future of mission critical workloads with the Western Digital Ultrastar DC SN861. The latest Western Digital SSD with cutting-edge PCIe® Gen5 enterprise-class speeds, the Ultrastar DC SN861 offers exceptional performance and multiple capacities up to 7.68TB<sup>1</sup>. With high random read speeds and low power consumption, the DC SN861 is optimized for compute-intensive AI and machine learning applications, ensuring superior read/write performance, extremely low latency, and maximize IOPs/Watt. The DC SN861 also provides a rich feature set including NVMe® 2.0 and OCP 2.0 support, 1 & 3 DWPD, and a 5-year limited warranty<sup>6</sup>, making it the ideal solution for hyperscale, cloud, and enterprise data centers.

## Features

### Ready for the Demands of AI Workloads

Designed to handle compute-intensive AI and machine learning applications which require high bandwidths and low latencies.

### Superior Performance and Capacity

Experience future-ready PCIe Gen5 read/write speeds with multiple capacities up to 7.68TB<sup>1</sup>.

### Designed for Power Efficiency

Architected to provide heightened performance per watt, optimizing power efficiency and reducing operational costs.

### Outstanding Mixed Workload Performance

High-speed random reads provide enhanced solutions at low cost for your enterprise.

### Optimized for Quality of Service (QoS)

Reduce latency during mission-critical workloads, delivering consistent Quality of Service (QoS) for your applications, even under heavy workloads.

### Rich Enterprise Features

Benefit from enterprise-class features such as Power Loss Protection, End-to-End Data Path Protection, and TCG security and encryption, helping ensure data integrity and security.

### Future-Ready Data Infrastructure

Designed to support NVMe 2.0, and NVMe MI 1.2c, and OCP 2.0 supportive, for enhanced scalability and efficiency.

# Ultrastar® DC SN861

Product Information						
Capacity <sup>1</sup>	1.60TB	1.92TB	3.20TB	3.84TB	6.40TB	7.68TB
Endurance <sup>2</sup>	3 DWPD	1 DWPD	3 DWPD	1 DWPD	3 DWPD	1 DWPD
Security	SE, ISE, TCG OPAL 2.01					
Form Factor	U.2					
Interface	PCIe Gen5×4					
NVMe Specification	NVMe v2.0					
Performance (projected)						
Read Throughput (max MB/s, Seq 128KiB) <sup>3</sup>	13,700	13,700	13,700	13,700	13,700	13,700
Write Throughput (max GB/s, Seq 256KiB) <sup>3</sup>	3,600	3,600	7,200	7,300	7,500	7,500
Read IOPS (max, Rnd 4KiB) <sup>3</sup>	2,100K	2,100K	3,300K	3,300K	3,000K	3,000K
Write IOPS (max, Rnd 4KiB) <sup>3</sup>	350K	165K	665K	320K	750K	390K
Read Latency (μS) <sup>4</sup>	70	70	70	70	70	70
Write Latency (μS) <sup>4</sup>	10	10	10	10	10	10
Reliability						
MTTF <sup>5</sup> (hours, projected)	2.5M					
Uncorrectable Bit Error Rate (UBER)	1 in 10 <sup>17</sup>					
Annualized Failure Rate <sup>5</sup> (AFR, projected)	0.35%					
Limited Warranty <sup>6</sup> (years)	5 years					
Power Management (projected)						
Requirement (DC, +/- 10%)	+12v					
Operating Modes (avg, max)	20W					
Idle (Average)	<5W					
Physical Size						
z-height (mm)	15mm					
Dimensions (width x length, mm)	69.85mm x 100.45mm					
Weight (g, max)	Not Available					
Environmental						
Operating Temperature (Ambient) <sup>7</sup>	0°C to 70°C					
Non-Operating Temperature <sup>8</sup>	-40°C to 85°C					
Ordering Information						
Security	1.60TB	1.92TB	3.20TB	3.84TB	6.40TB	7.68TB
SE	OTS2537	OTS2516	OTS2538	OTS2517	OTS2539	OTS2518
ISE	OTS2531	OTS2525	OTS2532	OTS2526	OTS2533	OTS2527
TCG Opal	OTS2534	OTS2528	OTS2535	OTS2529	OTS2536	OTS2530

<sup>1</sup> One megabyte (MB) is equal to one million bytes, one gigabyte (GB) is equal to 1,000MB (one billion bytes), one terabyte (TB) is equal to 1,000GB (one trillion bytes), and one petabyte (PB) is equal to 1,000TB. Actual user capacity may be less due to operating environment.

<sup>2</sup> NAND Endurance.

<sup>3</sup> Based on internal testing. Performance will vary by capacity point, or with the changes in useable capacity. Consult product manual for further details. All performance measurements are in full sustained mode and are peak values. IOPS = input/output operations persecond. Subject to change.

<sup>4</sup> Average random read latency at 4KiB, QD=1

<sup>5</sup> MTTF and AFR specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions for this drive model. MTTF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

<sup>6</sup> The warranty for the product will expire on the earlier of (i) the date when the flash media has reached one-percent (1%) of its remaining life or (ii) the expiration.

<sup>7</sup> Composite temperature reading

<sup>8</sup> Values are based on ambient temperature. Avoid non-operational exposure to temperatures in excess of 40°C for periods exceeding three months.

