



## Highlights

- World's first commercially available HDD with 11 disks
- Delivers industry leading capacity of up to 26TB<sup>1</sup> (CMR)
- Increases storage density without increasing footprint
- Maintains superior reliability of field-proven hardware designs
- Rated for 550TB/year workloads and up to 2.5M hours MTBF<sup>5</sup>

## Target Audience

- Data Center Managers
- IT Administrators
- Data Center Architects
- AI System Administrators

## Ideal for

- Hyperscalers and big data applications
- Artificial Intelligence training pools
- Cloud repatriation data pools
- Cloud service providers
- Converged infrastructures

## Ultrastar® DC HC590

Ultrastar® Data Center HC590 hard drives combine field-proven designs with the latest innovative technologies to meet customer demands for increased storage density in the existing storage footprint.

### The Future of More. Plus One.

The **world's first commercially available HDD with 11 disks** delivers unbeaten capacity of up to 26TB<sup>1</sup> to help quench customer's insatiable demand for increased storage density in the existing storage footprint.

### Rapid Qualification and Rock Solid Reliability

Leveraging **field-proven hardware and firmware designs** from generations of highly successful products ensures easy qualification, seamless integration and rapid adoption while maintaining superior dependability and reliability.

### Maximum Rack-Space Efficiency

The higher storage density provided by 11 disks combined with our exclusive **energy-assisted Perpendicular Magnetic Recording (ePMR)** technology, which increase tracks-per-inch (TPI), allows data centers to maximize their storage efficiency.

### Protected Against Vibration and Shock

Our exclusive **Rotational Vibration Safeguard (RVS)** uses dual sensors to anticipate and counteract disturbances, maintaining peak performance in high-vibration environments. Combined with **Dynamic Fly Height technology**, Western Digital offers exceptional drive reliability and protection from unexpected shock events.

### Engineered with Industry-Leading Technology

Western Digital's proprietary **OptiNAND™** technology leverages integrated **iNAND® embedded flash** to perform key housekeeping functions, freeing up more capacity and improving the overall drive performance.

### Powerful Performance and Resiliency

Choose **ArmorCache™** write cache disabled (WCD) mode for increased random write performance or select write cache enable (WCE) mode to protect cached data in case of Emergency Power Off (EPO) or unexpected power loss scenarios.

### Meet Eco Goals with Helium

The stable internal environment created by our **HelioSeal® technology** enables this high-capacity helium drive to deliver one of the lowest power profiles in the industry.

### Trusted Reliability, Quality and World-Class Support

As an **industry-leading hard drive manufacturer**, Western Digital stands behind their Ultrastar hard drives with the assurance of a **5-year limited warranty<sup>5</sup>** and world-class support services to help create environments for data to thrive.



	24TB SATA	24TB SAS	26TB SATA	26TB SAS
Model Number	WUH722624ALxyz	WUH722624ALxyz	WUH722626ALxyz	WUH722626ALxyz
Formatted capacity <sup>1</sup>	24TB	24TB	26TB	26TB
Recording Technology	CMR	CMR	CMR	CMR
Interface	SATA 6 Gb/s	SAS 12 Gb/s	SATA 6 Gb/s	SAS 12 Gb/s
Format: Sector size (bytes) <sup>2</sup>	512e: 512   4Kn: 4096	512e: 512   4Kn: 4096	512e: 512   4Kn: 4096	512e: 512   4Kn: 4096
Areal density (Gbits/sq. in.)	1100	1100	1190	1190
Performance				
Data buffer <sup>3</sup> (MB)	512	512	512	512
Rotational speed (RPM)	7200	7200	7200	7200
Latency average (ms)	4.16	4.16	4.16	4.16
Interface transfer rate (MB/s, max)	600	1200	600	1200
Sustained transfer rate <sup>4</sup> (MB/s) / (MiB/s, max)	287 / 274	287 / 274	302 / 288	302 / 288
Reliability/Data Integrity				
Error rate (non-recoverable, bits read)	1 in 10 <sup>15</sup>	1 in 10 <sup>15</sup>	1 in 10 <sup>15</sup>	1 in 10 <sup>15</sup>
Load/Unload cycles (at 40°C)	600,000	600,000	600,000	600,000
Availability (hrs/day x days/wk)	24x7	24x7	24x7	24x7
MTBF <sup>5</sup> (M hours, projected)	2.5	2.5	2.5	2.5
Annualized Failure Rate <sup>5</sup> (projected)	0.35%	0.35%	0.35%	0.35%
Limited warranty	5 years	5 years	5 years	5 years
Power				
Requirement	+5 VDC, +12VDC	+5 VDC, +12VDC	+5 VDC, +12VDC	+5 VDC, +12VDC
Random 50/50 Read/Write, 4KB QD=4 @MAX IOPS (W)	8.4	8.7	8.4	8.7
Idle <sup>6</sup> (W)	5.6	5.9	5.6	5.9
Power efficiency at idle (W/TB)	0.23	0.25	0.22	0.23
Acoustics				
Operating/Idle (Bels, typical)	3.2/2.5	3.2/2.5	3.2/2.5	3.2/2.5
Physical Dimensions				
z-height (max)	1.03 in. (26.1 mm)	1.03 in. (26.1 mm)	1.03 in. (26.1 mm)	1.03 in. (26.1 mm)
Length (max)	5.78 in. (146.7 mm)	5.78 in. (146.7 mm)	5.78 in. (146.7 mm)	5.78 in. (146.7 mm)
Width ± .01 in. (max)	4.0 in. (101.6 mm)	4.0 in. (101.6 mm)	4.0 in. (101.6 mm)	4.0 in. (101.6 mm)
Weight (lb/kg , ± 10%)	1.47 lb. (.67 kg) ± 10%	1.47 lb. (.67 kg) ± 10%	1.47 lb. (.67 kg) ± 10%	1.47 lb. (.67 kg) ± 10%
Environmental				
(Operating)			(Non-Operating)	
Temperature (°C) <sup>7</sup>	5° to 60°		Temperature (°C) <sup>7</sup>	-40° to 70°
Shock (half-sine wave 2 ms, G)	40		Shock (half-sine wave, G)	200
Vibration (G RMS 5 to 500 Hz)	0.7		Vibration (G RMS 2 to 200 Hz)	1.04

<sup>1</sup> One MB is equal to one million bytes, one GB is equal to one billion bytes and one TB equals 1,000GB (one trillion bytes). Actual user capacity may be less due to operating environment.

<sup>2</sup> Advanced Format drive: 4K (4096-byte) physical sectors.

<sup>3</sup> Portion of buffer capacity used for drive firmware.

<sup>4</sup> Based on internal testing; performance may vary depending on host environment, drive capacity, logical block address (LBA), and other factors. The location of the max rate is at approximately 10% into the capacity of the HDD. 1MiB = 1,048,576 bytes (2<sup>20</sup>), 1MB = 1,000,000 bytes (10<sup>6</sup>).

<sup>5</sup> Projected values. Final MTBF and AFR specifications will be based on a sample population and are estimated by statistical measurements and acceleration algorithms under typical operating conditions, typical workload and 40°C device-reported temperature. Derating of MTBF and AFR will occur above these parameters, up to 550TB/year and 60°C (device reported temperature). MTBF and AFR ratings do not predict an individual drive's reliability and do not constitute a warranty.

<sup>6</sup> Idle specification is based on use of Idle\_A.

<sup>7</sup> 5°C ambient temperature, 60°C device reported temperature.

How to Read the Ultrastar Model Number

WUH7226XXALxyz

W = Western Digital  
 U = Ultrastar  
 H = Helium (vs. S for Standard)  
 72 = 7200 RPM  
 26 = Maximum capacity  
 XX = Capacity this model  
   24 = 24TB  
   26 = 26TB  
 A = Generation code  
 L = z-height 26.1(mm)

xx = Interface  
 E6 = 512e SATA 6 Gb/s  
 52 = 512e SAS 12Gb/s  
 y = Power Disable Pin 3 status  
 0 = Power Disable Pin 3 support  
 L = Legacy Pin 3 config - no Power Disable  
 z = Data Security Mode  
 0 = Instant Secure Erase (ISE)  
 1 = SED\*: Self Encrypting Drive TCG-Enterprise and Sanitize Crypto Scramble Erase  
 4 = Base (SE)\*: No Encryption. Sanitize Overwrite only.  
 5 = SED-FIPS\*: Self Encrypting Drive TCG Enterprise FIPS  
 \*ATA Security Feature Set comes standard on ATA



5601 Great Oaks Parkway  
 San Jose, CA 95119, USA  
[www.westerndigital.com](http://www.westerndigital.com)

© 2024 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital design, the Western Digital logo, ArmorCache, Helioseal, iNAND, OptiNAND, and Ultrastar are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. Apache Hadoop is either a registered trademark or trademark of the Apache Software Foundation in the United States and/or other countries. All other marks are property of their respective owners. References in this publication to Western Digital products, programs, or services do not imply that they will be made available in all countries. Product specifications provided are sample specifications that are subject to change and do not constitute a warranty. Please visit the Support section of our website, [www.westerndigital.com](http://www.westerndigital.com), for additional information on product specifications. Pictures shown may vary from actual products.